

LED Spotlight PA LING Track 3

SPATIAL ENHANCE EFFECT



Dimmable



Ra>90



UGR<19



Superior Visual Comfort



Flexible



LED Spotlight PA LING Track 3



Dimmable



Ra>90



UGR<19



Superior Visual Comfort



Flexible

Specification

Item Code	Item Description	Power (W)	CCT (K)	Beam Angle	Product Size (mm) (LxWxH)
541001177700	LEDSpotTR-PA-LSL024005-24W-BK-24D-930-BLE2-D	24	3000	24°	φ90*132
541001177800	LEDSpotTR-PA-LSL024005-24W-BK-36D-930-BLE2-D	24	3000	36°	φ90*132
541001177900	LEDSpotTR-PA-LSL024005-24W-BK-24D-950-BLE2-D	24	5000	24°	φ90*132
541001178000	LEDSpotTR-PA-LSL024005-24W-BK-36D-950-BLE2-D	24	5000	36°	φ90*132

Technical Specification	
Life Time (L70B50)	30000
Colour Consistency (SDCM)	<5
Housing Color	Black
Ra	>90
Degree of protection (IP)	IP20
Driver Integrated	YES
Protection Class	I
Power Factor	0.9

Electrical Supply	
Frequency	50/60Hz
Nominal Voltage	220-240VAC

Mechanical Properties	
Housing Material	Aluminium
Optical Material	PMMA

Ambient Conditions	
Operating Temperature	-20-40°C

Packaging Information

Item		Outer box		
Item Code	Item Description	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Packing Qty (pcs/CTN)
541001177700	LEDSpotTR-PA-LSL024005-24W-BK-24D-930-BLE2-D	395*300*350	10.78	12
541001177800	LEDSpotTR-PA-LSL024005-24W-BK-36D-930-BLE2-D	395*300*350	10.78	12
541001177900	LEDSpotTR-PA-LSL024005-24W-BK-24D-950-BLE2-D	395*300*350	10.78	12
541001178000	LEDSpotTR-PA-LSL024005-24W-BK-36D-950-BLE2-D	395*300*350	10.78	12

Dimensional Drawing (mm)

